

G041 - NIMBLE

Mechanical Protection Polyurethane



EN 388:2003



4131

EN 388:2016



3131X

EN 420



"Following the new EU Regulation 2016/425 and the new standards on protective gloves EN 388:2016, EN ISO 374-1:2016, EN 374-2:2015 and EN 16523-1:2015, COFRA is re-certifying all its protective gloves. For this reason, it is possible that in our stock and on the market there are still gloves with the old standards EN 388:2003, EN 374-1:2003, EN 374-2:2003, EN 374-3:2003. COFRA guarantees that all the productions do not have technical and qualitative differences and are in compliance with the regulations in force"

Features	<ul style="list-style-type: none"> • Maximum dexterity and ease of movement • Maximum lightness and breathability • Recommended for little tools handling
-----------------	--

Coating	Polyurethane PU-DEX
----------------	---------------------

Lining	Nylon
---------------	-------

Gauge	13
--------------	----

Colour	Black/black
---------------	-------------

Application	Activities requiring superb hand dexterity, assembly, building and construction, industry, maintenance
--------------------	--

Sizes	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (XXL)
--------------	--------	-------	-------	-------	---------	----------

Lenght	21 cm	22 cm	23 cm	24 cm	25 cm	26 cm
	8,3"	8,7"	9"	9,5"	9,9"	10,2"




POLYURETHANE WITH SUPERIOR GRIP



Packaging	Code	Quantity
		G041-D100
	G041-DD00	1 dozen (1 bag containing 12 pairs)
	G041-K100	Carton containing 12 dozen (144 single packed gloves)
	G041-KD00	Carton containing 12 dozen (12 bags containing 12 pairs)



New polyurethane compound that turns around the concept of grip. The excellent grasp of little tools and the maximum dexterity enhance productivity in those jobs where maximum precision and accuracy are demanded.



SAFETY TECHNICAL SPECIFICATIONS

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 420:2003 + A1 2009 (par. 4.3.2)	pH determination	3,5 < pH < 9,5	6,7
UNI EN 14362-1/3:2012	Carcinogenic and aromatic amines	≤ 30 ppm	< 5

STANDARD	DESCRIPTION	LEVEL					LEVEL REACHED	
		1	2	3	4	5		
EN 388:2016 (par. 6.1)	Abrasion resistance (number of frictions)	≥ 100	≥ 500	≥ 2000	≥ 8000	-	3	
EN 388:2016 (par. 6.2)	Cutting test : blade cut resistance (index)	≥ 1,2	≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	1	
EN 388:2016 (par. 6.4)	Tear resistance (N)	≥ 10	≥ 25	≥ 50	≥ 75	-	3	
EN 388:2016 (par. 6.5)	Puncture resistance (N)	≥ 20	≥ 60	≥ 100	≥ 150	-	1	
EN 388:2016 (par. 6.3) - EN ISO 13997	TDM : cutting resistance (N)	A	B	C	D	E	F	
		≥ 2	≥ 5	≥ 10	≥ 15	≥ 22	≥ 30	X
EN 388:2016 (par. 6.6) - EN 13594:2015	Impact protection	P			ABSENT			ABSENT
		Achieved			Test not executed			

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved.