

# Information for users

EN

EN 420+A1:2009 EN 388:2003

PPE CATEGORY II



Read the instructions carefully.

In accordance with the requirements of the Regulation (EU) 2016/425

**Product:** Nylon gloves, seamless knit liner, palm and fingers MICROFOAM nitrile with PU dots, breathable.

<b>Design:</b>	„NAPA“	<b>Code:</b>	3410 003 710 XX	<b>Size:</b>	7, 8, 9, 10	<b>Production pattern:</b>	1011004
<b>Material:</b>	97% Nylon, 3% Elastane – Spandex, coated palm and fingers nitrile with breathable finish MICROFOAM with PU dots.						

**Purpose:** The basic function of the gloves is protection against injuries that may occur in working areas for which the product is designed. They may serve as a protection of hands against dirt and protection in the working areas where workers have to face mechanical hazards.

The gloves were tested in accordance with EN 388 - mechanical hazards (The higher the number, the higher the protection factor)				
A (0-4)	Abrasion resistance	Performance level 4	 A.B.C.D	The protection works only against the specified hazards. Do not use the gloves as a protection against different hazards and classes. The results apply only for the model classes, not for the protection levels (classes). The protection levels (classes) are determined based on the tests carried out in accordance with the conditions determined in the valid standards specified above. The protection levels (classes) apply only for new gloves not washed or cleaned.
B (0-5)	Blade cut resistance (coupe test)	Performance level 1		
C (0-4)	Tear resistance	Performance level 2		
D (0-4)	Puncture resistance	Performance level 1		
EN 420 - protective gloves (general requirements)				
(1-5)	Dexterity	Performance level 5		
„X“ = test not performed or not applicable..				

**Please note:** The user must check the gloves before and after use to verify that they are in the required condition. Do not use as a protection against different hazards and classes. Do not use the gloves for handling with sharp objects, flames or hot or heated objects, toxic chemicals or greasy objects. Not resistant to soaking. It is not allowed to wear these gloves in cases with risk of entanglement with moving parts of machines. The gloves comply with the requirements for puncture resistance. However, they are not meant for protection against thin, sharp objects, such as injection needles. The mentioned facts may help the user for rational use of this type of protective gloves. It is the responsibility of every user to judge, whether the gloves are used in suitable conditions.

**Maintenance, lifetime:** After use, make sure the gloves are removed from all pollutants. To prolong the life of the glove. The gloves are designed for single or short-term use only. Damp gloves should be dried out at a room temperature. Gloves should not be washed. Any dirt should be brushed out using a soft brush, nitrile Wipe with a damp cloth. Do not clean chemically, bleach, dry in a tumble dryer, or iron. The gloves that are worn through, have holes burned through, or are hard must be replaced. We are not responsible for possible reduction of the protective function caused by improper maintenance. Under suitable storage conditions, shelf life is 2 years.

**Storing and transport:** Storing in a clean, dry and ventilated place at the room temperature, without any contamination by moisture, dirt, mould, or other agents reducing the level of protection. Do not expose it to solar radiation. The supplier doesn't provide warranty for such damage. Carry them preferably in original package.

**Accessories:** The product is supplied without accessories.

**Dangerous admixtures:** The gloves contain allergen - Latex. They may cause an allergic reaction if used by sensitive people, including anaphylactic shock. If skin irritation or allergic reaction do not use gloves and contact your doctor immediately.

**Disposal:** used gloves can be contaminated with infectious materials or other dangerous substances - dispose of them in compliance with the Act on Waste.

The Notified Body that performs conformity assessment:

Notified Body No. 0075, CTC 4 rue Hermann Frenkel 69367 Lyon cedex 07 France.

The Declaration of Conformity can be found here: [www.canis.cz](http://www.canis.cz); for individual products, in the bar "Documents to download".

<b>Marking - example:</b>		
„NAPA“	Type of gloves	
7	Size	
EN388 	Pictogram and number of the standard that the product complies with	
4121	Results of the tests carried out	
CE	Conformity mark	
cat II	Glove category	
	Notice on the necessity to read the instructions for use	
„A“	Production identification	
1011004	Design production	
ZA/2018/251	Lot	
	Manufacturer identification	

If you need more information, please contact:



Poděbradská 260/59, Hloubětín, 198 00 Praha 9, Czech Republic

# Information for users

EN

EN 420+A1:2009 EN 388:2016+A1:2018

PPE CATEGORY II



Read the instructions carefully.

In accordance with the requirements of the Regulation (EU) 2016/425

**Product:** Nylon gloves, seamless knit liner, palm and fingers MICROFOAM nitrile, breathable.

<b>Design:</b>	„NAPA“	<b>Code:</b>	3410 003 710 XX	<b>Size:</b>	6, 7, 8, 9, 10, 11, 12
<b>Material:</b>	Nylon/Elastane – Spandex, coated palm and fingers Nitrile with breathable finish MICROFOAM with Nitrile dots.				

**Purpose:** They may serve as a protection of hands against dirt and protection in the working areas where workers have to face minor mechanical hazards (abrasions, soiling...), for example: logistics, warehousing, construction, hobby, work with slippery objects, automotive, municipal services, garden, assembly and packaging of small parts. Put the gloves on dry, clean hands.

The gloves were tested in accordance with EN 388 - mechanical hazards (The higher the number, the higher the protection factor)					
A (0-4)	Abrasion resistance:	Performance level	4	 A.B.C.D.E.F	The protection works only against the specified hazards. Do not use the gloves as a protection against different hazards and classes. The results apply only for the model classes, not for the protection levels (classes). The protection levels (classes) are determined based on the tests carried out in accordance with the conditions determined in the valid standards specified here. As for the gloves with two or more layers it does not necessarily reflect the properties of the outer layer. The protection levels (classes) apply only for new gloves not washed or cleaned.
B (0-5)	Blade cut resistance (coupe test)	Performance level	1		
C (0-4)	Tear resistance	Performance level	3		
D (0-4)	Puncture resistance	Performance level	1		
E (A-F)	Cut Resistance (TDM)	Performance level	X		
F(P/X) or nothing	Impact protection	Performance level	X		
EN 420 - protective gloves (general requirements)					
(1-5)	Dexterity	Performance level	5		
„X“ = test not performed or not applicable..					

**Please note:** The user must check the gloves before and after use to verify that they are in the required condition. Do not use as a protection against different hazards and classes. Do not use the gloves for handling with sharp objects, flames or hot or heated objects, toxic chemicals or greasy objects. Not resistant to soaking.

It is not allowed to wear these gloves in cases with risk of entanglement with moving parts of machines. Due to the dulling of the blade during the cut resistance test (B) the results of the cut tests are only indicative, while the TDM (E) cut resistance test is the result of the reference design. The gloves comply with the requirements for puncture resistance. However, they are not meant for protection against thin, sharp objects, such as injection needles. The mentioned facts may help the user for rational use of this type of protective gloves. It is the responsibility of every user to judge, whether the gloves are used in suitable conditions.

**Maintenance, lifetime:** After use, make sure the gloves are removed from all pollutants. To prolong the life of the glove. The gloves are designed for single or short-term use only. Damp gloves should be dried out at a room temperature. Gloves should not be washed. Any dirt should be brushed out using a soft brush, nitrile Wipe with a damp cloth. Do not clean chemically, bleach, dry in a tumble dryer, or iron. The gloves that are worn through, have holes burned through, or are hard must be replaced. We are not responsible for possible reduction of the protective function caused by improper maintenance. Under suitable storage conditions, shelf life is 2 years.

**Storing and transport:** Storing in a clean, dry and ventilated place at the room temperature, without any contamination by moisture, dirt, mould, or other agents reducing the level of protection. Do not expose it to solar radiation. The supplier doesn't provide warranty for such damage. Carry them preferably in original package.

**Accessories:** The product is supplied without accessories.

**Dangerous admixtures:** The gloves may contain an allergen - Latex. They may cause an allergic reaction if used by sensitive people, including anaphylactic shock. If skin irritation or allergic reaction do not use gloves and contact your doctor immediately.

**Disposal:** used gloves can be contaminated with infectious materials or other dangerous substances - dispose of them in compliance with the Act on Waste.

The Notified Body that performs conformity assessment:

Notified Body No. 0075, CTC 4 rue Hermann Frenkel 69367 Lyon cedex 07 France.

The Declaration of Conformity can be found here: [www.canis.cz](http://www.canis.cz); for individual products, in the bar "Documents to download".

<b>Marking (sample) - description:</b>			
NAPA	Type of gloves		Symbol indicating the necessity to read the instructions
10	Size	„A“	Identification production
	Pictogram and number of the standard that the product complies with		Manufacturer identification
4131X	Results of the tests carried out	X/2020	Month and year of production
	Conformity mark	ZA/2020/XXX CAT II	Lot - Mark / year / number Glove category

If you need more information, please contact:



Poděbradská 260/59, Hloubětín, 198 00 Praha 9, Czech Republic.