


BLACK KITE				
Description	A basic harness, easy to fit and adjust.			
Standard	EN361:2002			
Attachment Points		Device with a single dorsal attachment point for fall arrest. The large, functional dorsal hook is made of forged steel.		
Adjustment	SINGLE - on the lower part of the harness			
Metal components	Zinc-plated steel			
Straps	45 mm and 30 mm wide polyester			
Plus	EXTREME LOAD 150 kg 	The additional test certifies the resistance of Cofra devices against a maximum nominal load of 150 kg, compared with the 100 kg of the normal devices on the market.		
	HIGH-TENACITY POLYESTER STRAP 	The strap is made of high-tenacity polyester making it highly resistant to tear and abrasion.		
	STEEL COMPONENTS 	Steel resists perfectly to the considerable stresses which develop during a fall. All steel components have undergone anticorrosive galvanisation treatment with zinc or chrome.		
Packaging	Code	Size	Quantity	Weight (pc.)
	A000-1100.I2	M-2XL (one size)	1 pc.	750 g
	A000-K100.I2		25 pcs.	

SIZE CHART

SIZE	HARNESS			
	A (cm)	B (cm)	C (cm)	H (cm)
M-2XL	96/116	84/104	56/70	172/190



The diagram shows a stylized human figure from the waist up, wearing a harness. Four measurement points are marked with red boxes and letters: 'A' at the chest, 'B' at the waist, 'C' at the hip, and 'H' at the height from the waist to the top of the harness. A vertical line with arrows at both ends indicates the height measurement 'H'.

STOCKING CONDITIONS AND MAINTENANCE

Lifetime	The lifetime of the unused metal products is unlimited. The lifetime of the unused not metal products is 10 years under normal conditions. Once the product is used, its lifetime cannot be estimated since there are factors which could considerably reduce its lifetime such as: intense use; damage to product components; contact with chemical substances; high temperatures, abrasions, cuts, violent impacts, wrong use and stockage.
Cleaning	Cleaning the textile and plastic parts: wash only with cold fresh water and neutral soap and allow to air dry, away from direct sources of heat. Cleaning the metallic parts: wash with cold fresh water and dry. If the equipment becomes wet either during use or after cleaning, it must be left to air dry and kept away from direct heat.
Transport and stocking	Keep the device in its original packaging. During transport and storage, keep this product away from light and sources of heat, from high humidity, from sharp edges or objects, from corrosive substances and from any other possible cause of damage or deterioration, in order to preserve the performance and safety of the product. Keep this product in a cool, dry place to preserve the performance and safety of the product.