



Prod. Ref. 78400-001
Safety cat. S1 P SRC
Range of sizes 39 - 47 (6 - 12)
Weight (sz. 8) 510 g
Shape A
Width 11

Description: Blue jeans breathable textile and suede leather shoe, **SANY-DRY®** lining, antistatic, anti-shock, slipping resistant, non metallic **APT Plate** midsole **Zero Perforation**.

Plus: **COFRA SOFT** footbed, made of scented polyurethane, holed, antistatic, anatomic, soft and comfortable; the shape of the bottom part guarantees impact energy absorption (shock absorber) and high grip; the upper part absorbs moisture and keeps the foot dry. Perfumed sole

Suggested uses: Warehouses , transportation sector, industries.

Care and maintenance: Clean after each use and dry off away from direct heat; treat the leather with a suitable shoe-polish. Avoid contact with aggressive chemicals or extreme temperature. Avoid immersion in sea water, lime water or cement mixed with water.

MATERIALS / ACCESSORIES

SAFETY TECHNICAL SPECIFICATIONS

		Clause EN ISO 20345:2011	Description	Unit	Cofra result	Requirement
Complete shoe	Toe cap: ALUMINIUM made, ultra light, impact resistant until 200 J	5.3.2.3	Shock resistance (clearance after shock)	mm	15,5	≥ 14
	and compression resistant until 1500 kg	5.3.2.4	Compression resistance (clearance after compression)	mm	15	≥ 14
	Anti perforation midsole: in multi-layers highly tensile fabric, penetration resistant, Zero Perforation	6.2.1	Penetration resistance	N	To 1100 N	≥ 1100
		No perforation				
Antistatic shoe: the bottom is fit for the dissipation of electrostatic charges		6.2.2.2	Electric resistance			
			- wet	MΩ	460	≥ 0.1
			- dry	MΩ	788	≤ 1000
Energy absorption system		6.2.4	Shock absorption	J	27	≥ 20
Upper	Blue jeans breathable textile	5.4.6	Water vapour permeability	mg/cmq h	> 2	≥ 0,8
			Permeability coefficient	mg/cmq	> 16,3	> 15
Upper	Light blue suede leather thickness 1,6/1,8 mm	5.4.6	Water vapour permeability	mg/cmq h	> 4,7	≥ 0,8
			Permeability coefficient	mg/cmq	> 46,9	> 15
Vamp	Textile, breathable, abrasion resistant, colour black	5.5.3	Water vapour permeability	mg/cmq h	> 6	≥ 2
lining	Thickness 1,2 mm		Permeability coefficient	mg/cmq	> 48	≥ 20
Quarter	SANY-DRY® , breathable, antibacterial, abrasion resistant, colour blue thickness 1,2 mm	5.5.3	Water vapour permeability	mg/cmq h	> 9,8	≥ 2
			Permeability coefficient	mg/cmq	> 78,5	≥ 20
Sole	Antistatic Polyurethane/TPU directly injected in the upper: Outsole: Ice TPU, slipping resistant, abrasion resistant and hydrocarbons resistant. Midsole: Blue polyurethane, low density, comfortable and anti-shock.	5.8.3	Abrasion resistance (lost volume)	mm³	35	≤ 150
		5.8.4	Flexing resistance (cut increase)	mm	1	≤ 4
		5.8.5	Interlayer bond strength	N/mm	> 5	≥ 4
		6.4.2	Hydrocarbons resistance (ΔV = volume increase)	%	-0,8	≤ 2
	Adherence coefficient of the sole	5.3.5	SRA : ceramic + detergent solution – flat		0,60	≥ 0,32
			SRA : ceramic + detergent solution – heel (contact angle 7°)		0,51	≥ 0,28
			SRB : steel + glycerol – flat		0,27	≥ 0,18
			SRB : steel + glycerol – heel (contact angle 7°)		0,19	≥ 0,13