

TECHNICAL SHEET

CABRIES – trousers

Description

- 2 front pockets,
- 2 back pockets,
- hammer loop,
- good resistance to washings,
- good resistance to abrasion,
- cuffs on the bottom of the trousers,
- rivets and bar tacks in the most stressed areas to guarantee durability,
- knee and leg ergonomic design,
- left side pocket with flap,
- coin pocket,
- rule pocket,
- stretch fabric,
- triple stitching on parts subject to wear,
- YKK® zip.



Maintenance

Maximum wash temperature: 40 °C; Do not bleach; Dry clean with solvents on point F plus Tetrachloroethylene; Tumble drying possible - Drying at lower temperature; Ironing at low temperature (max 110 °C).









Item

V495-0-00 blue

Standards:

Sizes

44 - 64

SAFETY TECHNICAL SPECIFICATIONS

	Test method	Description	Cofra result	Minimum requirement / range
Background	EN ISO 1833-1977, SECTION 10	Composition:	Cotton 70%,	
fabric			Polyester 28%,	
			Elastane 2%	
	EN ISO 12127:1996	Fabric mass per unit area	330 ±5% g/m ²	
	EN ISO 13688:2013	Dimensional change	warp: -0.7%	±3%
	5.3 ISO 5077:2007/ ISO 6330	(4N-40°C)	weft: -0.8%	
	EN ISO 13688:2013 4.2 (ISO 3071)	The pH's determination from the watery extract	pH=5,3	3,5 ≤pH≤ 9,5
	EN ISO 13688:2013 4.2 (EN 14362-1)	Search of the aromatic and carcinogenic amines	Not recording	≤30 ppm
	EN ISO 13934-1	Tensile strength	Warp: 940 N Weft: 860 N	

Made by Workwear Technical Dept.

Version 1.0 date 19/09/2017 Drafts, rules, tables, data, directives and others informations here contained or attached to this document, are owned only by Cofra s.r.l. and must not be given or disclosed to any third party. It shall be prohibited to give, to share and to copy data contained in this notice and its relative attached documents by any subject different from the recipient according to both Article 616 of Penal Code and Personal Data Protection Code (Italian Legislative Degree n.196/2003). According to Article 98 and Article 99 of C.P.I, Cofra s.r.l will act through civil, administrative, or penal sanctions in respect of perpetrators in deference to articles 1 2 4 and successive ones of C.P.I. In case of dispute Italian exclusive jurisdiction will be apply as well as the competent court will be that one where Cofra s.r.l. has its registered office



TECHNICAL SHEET

O WORK	LOTINIOAL GITLLI			
EN ISO 13937-2	Tearing strenght	Warp: 28 N		
		Weft: 36 N		
EN ISO 12947-2	Determination of the abrasion resistance of fabrics by the Martindale method	28300 cycles		
ISO 105-C06	Colour fastness to Laundering at 40°C			1 - 5
	Colour change	4-5		
	Staining:			
	diacetate	4-5		
	cotton	4-5		
	nylon	4-5		
	polyester	4-5		
	acrylic	4-5		
	wool	4-5		
ISO 105 D01	Colour fastness to dry cleaning			
	Colour change	4-5		1 - 5
	Staining:			
	diacetate	4-5		
	cotton	4		
	nylon	4-5		
	polyester	4-5		
	acrylic	4-5		
	wool	4-5		
EN ISO 105 E04	Colour fastness to perspiration	Acidic	Alkaline	
	Colour change	4-5	4-5	1 - 5
	Staining:			
	diacetate	4-5	4	
	cotton	4-5	4	
	nylon	4-5	4-5	
	polyester	4-5	4-5	
	acrylic	4-5	4-5	
	wool	4-5	4-5	
ISO 105-X12	Colour fastness to rubbing			1-5
	Staining:	Dry: 4 - 5 Wet: 2 - 3		
ISO 105-X11	Colour fastness to hot pressing			
	Colour change	Dry: 4 - 5		
		Wet: 4 - 5		