

G004 - CLING Mechanical Protection Nitrile













"It is possible that gloves marked with previous standards are despatched. Cofra grants that all productions do not have technical and quality differences."

Features

- High resistance to oils
- Excellent grip on dry surfaces

Coating	Smooth nitrile
---------	----------------

Polyester Lining

Gauge 13

Colour Grey/black

Mechanical industry, building and construction, **Application** agriculture

Sizes	(S)	(M)	(L)	(XL)	(XXL)
Longht	23 cm	24 cm	25 cm	26 cm	27 cm
Lenght	9"	9,5"	9,9"	10,2"	10,6"



EXCELLENT GRIP ON DRY SURFACES



	(Code				Quantity			
	G00	4-D100	1 do	1 dozen (12 single packed gloves)					
Packaging	G00	4-DD00	1 do	zen (1 bag	containing	12 pairs)			
G004-K100 Carton containing 12 dozen (144 single packed gloves)					n (144 single packed gloves)				
	G00	4-KD00	Cart	Carton containing 12 dozen (12 bags containing 12 pairs)					





SAFETY TECHNICAL SPECIFICATIONS

The PPE is in compliance with essential requirements of (EU) 2016/425 regulation

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 420:2003 + A1 2009	pH determination	3,5 < pH < 9,5	7,05
UNI EN 14362-1/3:2012	Carcinogenic and aromatic amines	≤ 30 ppm	NOT RECORDING
EN ISO 21420:2020	Further technical specifications applied	COMPLIANT / NOT COMPLIANT	COMPLIANT

STANDARD DESCRIPTION					LEVEL			LEVEL
STANDARD	DESCRIPTION		1	2	3	4	5	REACHED
EN 388:2016+A1:2018	Abrasion resistance (number of frictions)			≥ 500	≥ 2000	≥ 8000	-	3
EN 388:2016+A1:2018	Cutting test : blade cut resistance (ind	≥ 1,2	≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	1	
EN 388:2016+A1:2018	Tear resistance (N)	≥ 10	≥ 25	≥ 50	≥ 75	-	4	
EN 388:2016+A1:2018	Puncture resistance (N)	≥ 20	≥ 60	≥ 100	≥ 150	-	2	
EN 388:2016+A1:2018 - EN ISO 13997	TDM : cutting resistance (N)	Α	В	С	D	Е	F	X
		≥ 2	≥ 5	≥ 10	≥ 15	≥ 22	≥ 30	
EN 388:2016+A1:2018 - EN 13594:2015	Impact protection	P		ABSENT			ABSENT	
	Impact protection		Achieved			not exec		

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved