

G108 - CORBEL

Mechanical Protection Leather



Features

- Palm and back made of buffalo full grain leather providing the glove with great resistance
- The seamless palm makes the glove more comfortable and avoids blisters

Palm

Buffalo full grain leather

Back

Buffalo full grain leather

Leather Thickness

0,8 ÷ 1,0

The thickness of the material is not validating and it is not guaranteed, therefore any thickness variation cannot be reason of complaint, in consideration of the high variability of leather

RESISTANT AND COMFORTABLE

Cuff

Elastic band on the back

Colour

White/white

Application

Building and construction, mechanical industry, agriculture

Sizes

8 (M)	9 (L)	10 (XL)	11 (XXL)
-------	-------	---------	----------

Lenght

24 cm	25 cm	26 cm	27 cm
9,5"	9,9"	10,2"	10,6"



Packaging

Code

Quantity

G108-DD00

1 dozen (1 bag containing 12 pairs)

G108-KD00

Carton containing 12 dozen (12 bags containing 12 pairs)

SAFETY TECHNICAL SPECIFICATIONS

The PPE is in compliance with essential requirements of (EU) 2016/425 regulation

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 420:2003 + A1 2009	pH determination	3,5 < pH < 9,5	4,10
EN 420:2003 + A1 2009	Chromium VI determination	≤ 10 mg/kg	NOT RECORDING
UNI EN ISO 17234-1:2015	Carcinogenic and aromatic amines (leather)	≤ 30 ppm	NOT RECORDING
EN ISO 21420:2020	Further technical specifications applied	COMPLIANT / NOT COMPLIANT	COMPLIANT

STANDARD	DESCRIPTION		LEVEL					LEVEL REACHED
			1	2	3	4	5	
EN 388:2016+A1:2018	Abrasion resistance (number of frictions)		≥ 100	≥ 500	≥ 2000	≥ 8000	-	2
EN 388:2016+A1:2018	Cutting test : blade cut resistance (index)		≥ 1,2	≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	1
EN 388:2016+A1:2018	Tear resistance (N)		≥ 10	≥ 25	≥ 50	≥ 75	-	3
EN 388:2016+A1:2018	Puncture resistance (N)		≥ 20	≥ 60	≥ 100	≥ 150	-	2
EN 388:2016+A1:2018 - EN ISO 13997	TDM : cutting resistance (N)	A	B	C	D	E	F	X
		≥ 2	≥ 5	≥ 10	≥ 15	≥ 22	≥ 30	
EN 388:2016+A1:2018 - EN 13594:2015	Impact protection	P			ABSENT			ABSENT
		Achieved			Test not executed			

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved