



Prod. Ref.	TN140-000
Safety cat.	S1 P SRC
Range of sizes	36 - 48 (3 - 13)
Weight (sz. 8)	525 g
Shape	A
Widht (3 - 6)	10,5
Widht (6,5 - 13)	11

Description: Blue/light blue highly breathable textile shoe, **TRAI-Tex** 100% polyester fabric lining, anti-shock, antistatic, slipping resistant, non metallic **APT Plate** midsole **Zero Perforation**

Plus: METAL FREE. EVANIT footbed, made of EVA and nitrile special compound, with high bearing capacity and variable thickness. Thermoformed, punched and coated with highly breathable fabric. Antistatic thanks to a specific treatment on the surface and to seams made of conductive yarns

Suggested uses: Warehouses, transportation sector, industries

Care and maintenance: Clean after each use and dry off away from direct heat. Avoid contact with aggressive chemicals or extreme temperature. Avoid immersion in sea water, lime water or cement mixed with water

MATERIALS / ACCESSORIES

SAFETY TECHNICAL SPECIFICATIONS

		Clause EN ISO 20345:2011	Description	Unit	Cofra result	requirement
Complete shoe	Toe cap: non metallic FIBERGLASS toe cap, impact resistant until 200 J and compression resistant until 1500 kg	5.3.2.3	Shock resistance (clearance after shock)	mm	15,5	≥ 14
		5.3.2.4	Compression resistance (clearance after compression)	mm	19,5	≥ 14
	Anti perforation midsole: in multi-layers highly tensile fabric, penetration resistant, Zero Perforation	6.2.1	Penetration resistance	N	To 1100 N No Perforation	≥ 1100
	Antistatic shoe: the bottom is fit for the dissipation of electrostatic charges	6.2.2.2	Electric resistance			
			- wet	MΩ	70,2	≥ 0.1
			- dry	MΩ	290	≤ 1000
	Energy absorption system	6.2.4	Shock absorption	J	35	≥ 20
Upper	Blue/light blue highly breathable textile	5.4.6	Water vapour permeability	mg/cmq h	> 2,9	≥ 0,8
			Permeability coefficient	mg/cmq	> 27,1	> 15
Vamp	Textile, breathable, abrasion resistant, colour black	5.5.3	Water vapour permeability	mg/cmq h	> 4,2	≥ 2
			Permeability coefficient	mg/cmq	> 47,7	≥ 20
lining	Thickness 1,2 mm	5.5.3	Water vapour permeability	mg/cmq h	> 4,1	≥ 2
			Permeability coefficient	mg/cmq	> 47,2	≥ 20
Quarter	TRAI-Tex fabric, three-dimensional, breathable, abrasion resistant, colour grey	5.5.3	Water vapour permeability	mg/cmq h	> 4,1	≥ 2
			Permeability coefficient	mg/cmq	> 47,2	≥ 20
lining	thickness 1,2 mm	5.8.3	Abrasion resistance (lost volume)	mm ³	98	≤ 150
Sole	Outsole: black, high density, slipping resistant, abrasion resistant and hydrocarbons resistant,	5.8.4	Flexing resistance (cut increase)	mm	4	≤ 4
		5.8.5	Interlayer bond strength	N/mm	4,1	≥ 3
	Midsole: grey, low density, comfortable and anti-shock	6.4.2	Hydrocarbons resistance (ΔV = volume increase)	%	8	≤ 12
	Adherence coefficient of the sole	5.3.5	SRA : ceramic + detergent solution – flat		0,33	≥ 0,32
			SRA : ceramic + detergent solution – heel (contact angle 7°)		0,30	≥ 0,28
			SRB : steel + glycerol – flat		0,18	≥ 0,18
			SRB : steel + glycerol – heel (contact angle 7°)		0,15	≥ 0,13