




**JEMBER – trousers**

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                |                                                                                                                                                                            |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p><b>Description</b></p> | <ul style="list-style-type: none"> <li>• 2 wide front pockets,</li> <li>• double back pocket with flap closed with snap,</li> <li>• fabric with high elastic perception,</li> <li>• hammer loop,</li> <li>• knee and leg ergonomic design,</li> <li>• left side pocket with double opening (with snap and zip closure),</li> <li>• right side pocket closed with snap,</li> <li>• availability in single bag (V567-0) and / or in box (V567-1).</li> </ul> |                              |                                                                                                                                                                            |
| <p><b>Maintenance</b></p> | <p>Maximum wash temperature: 40 °C; Do not bleach ; Dry clean with solvents on point F plus Tetrachloroethylene; Tumble drying possible - Drying at lower temperature; Drying in the shade; Ironing at low temperature (max 110 °C).</p>                                                                                                                                | <p><b>Item</b></p>                                                                                             | <p>V567-0-00 KHAKI/BLACK<br/>V567-0-01 AVION/ BLACK<br/>V567-0-02 NAVY/ BLACK<br/>V567-0-03 CLAY BROWN/ BLACK<br/>V567-0-04 ANTHRACITE/BLACK<br/>V567-0-05 BLACK/BLACK</p> |
| <p><b>Standards:</b></p>  |                                                                                                                                                                                                                                                                                                                                                                                                                                                            | <p>EN ISO 13688:2013</p>  |                                                                                                                                                                            |
| <p><b>Sizes</b></p>       |                                                                                                                                                                                                                                                                                                                                                                                                                                                            | <p>44 – 64</p>                                                                                                 |                                                                                                                                                                            |

**SAFETY TECHNICAL SPECIFICATIONS**

|                                 | Test method                                       | Description                                           | Cofra result                                        | Minimum requirement / range |
|---------------------------------|---------------------------------------------------|-------------------------------------------------------|-----------------------------------------------------|-----------------------------|
| <p><b>Background fabric</b></p> | <p>EN ISO 1833-1977, SECTION 10</p>               | <p>Composition:</p>                                   | <p>60% cotton<br/>37% polyester<br/>3% elastane</p> |                             |
|                                 | <p>EN ISO 12127:1996</p>                          | <p>Fabric mass per unit area</p>                      | <p>245 g/m<sup>2</sup></p>                          |                             |
|                                 | <p>EN ISO 13688:2013<br/>4.2<br/>(ISO 3071)</p>   | <p>The pH's determination from the watery extract</p> | <p>OEKO-TEX<sup>®</sup> Standard 100</p>            | <p>3,5 ≤pH≤ 9,5</p>         |
|                                 | <p>EN ISO 13688:2013<br/>4.2<br/>(EN 14362-1)</p> | <p>Search of the aromatic and carcinogenic amines</p> | <p>OEKO-TEX<sup>®</sup> Standard 100</p>            | <p>≤30 ppm</p>              |
|                                 | <p>EN ISO 13688:2013<br/>5.3<br/>(ISO 5077)</p>   | <p>Dimensional change to washing (40°C)</p>           | <p>warp: -1.3%<br/>weft: 0.9%</p>                   | <p>±3%</p>                  |

|                |                                                                                                                                                   |                                                  |                                                    |     |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------|-----|
| ISO 105-C06    | Colour fastness to Laundering at 40°C<br><i>Colour change</i><br><i>Staining:</i><br>diacetate<br>cotton<br>nylon<br>polyester<br>acrylic<br>wool | 4-5<br>4-5<br>4-5<br>4-5<br>4-5<br>4-5           |                                                    | 1-5 |
| ISO 105 D01    | Colour fastness to to dry cleaning<br><i>Colour change</i><br><i>Staining:</i><br>diacetate<br>cotton<br>nylon<br>polyester<br>acrylic<br>wool    | 4-5<br>4-5<br>4-5<br>4-5<br>4-5<br>4-5           |                                                    | 1-5 |
| ISO 105 E04    | Colour fastness to perspiration<br><i>Colour change</i><br><i>Staining:</i><br>diacetate<br>cotton<br>nylon<br>polyester<br>acrylic<br>wool       | Acidic<br>4-5<br>4-5<br>4-5<br>4-5<br>4-5<br>4-5 | Alkaline<br>4-5<br>4-5<br>4-5<br>4-5<br>4-5<br>4-5 | 1-5 |
| ISO 105-X12    | Colour fastness to rubbing                                                                                                                        | Dry: 4-5<br>Wet: 3-4                             |                                                    | 1-5 |
| EN ISO 105-X11 | Colour fastness to hot pressing (110°C);<br><i>Colour change</i>                                                                                  | Dry: 4-5<br>Wet: 4-5                             |                                                    | 1-5 |
| ISO 105-B02    | Colour fastness to light<br><i>Colour change:</i>                                                                                                 | 4                                                |                                                    | 1-5 |
| EN ISO 13934-1 | Tensile strength                                                                                                                                  | warp: 1600 N<br>weft: 6 20 N                     |                                                    |     |
| EN ISO 13937-2 | Tear strenght                                                                                                                                     | warp: 44 N<br>weft: 51 N                         |                                                    |     |
| ISO 12947-2    | Determination of the abrasion resistance of fabrics by the Martindale method                                                                      | >30000 cycles                                    |                                                    |     |