




KUDUS – trousers

<p>Description</p>	<ul style="list-style-type: none"> • 2 wide front pockets, • double back pocket with flap closed with snap, • fabric with high elastic perception, • hammer loop, • knee and leg ergonomic design, • nylon adjustable kneepad pockets, • nylon external nail pockets, detachable with zip, • ruler pocket with tool holder loops, • side pocket with double opening (with velcro and zip closure), • availability in single bag (V568-0) and / or in box (V568-1). 		
<p>Maintenance</p>	<p>Maximum wash temperature: 40 °C; Do not bleach ; Dry clean with solvents on point F plus Tetrachloroethylene; Tumble drying possible - Drying at lower temperature; Drying in the shade; Ironing at low temperature (max 110 °C).</p> 	<p>Item</p>	<p>V568-0-00 KHAKI/BLACK V568-0-01 AVION/ BLACK V568-0-02 NAVY/ BLACK V568-0-03 CLAY BROWN/ BLACK V568-0-04 ANTHRACITE/BLACK V568-0-05 BLACK/BLACK</p>
<p>Standards:</p>		<p>EN ISO 13688:2013</p>	
<p>Sizes</p>		<p>44 – 64</p>	

SAFETY TECHNICAL SPECIFICATIONS

	<i>Test method</i>	<i>Description</i>	<i>Cofra result</i>	<i>Minimum requirement / range</i>
<p>Background fabric</p>	<p>EN ISO 1833-1977, SECTION 10</p>	<p>Composition:</p>	<p>60% cotton 37% polyester 3% elastane</p>	
	<p>EN ISO 12127:1996</p>	<p>Fabric mass per unit area</p>	<p>245 g/m²</p>	
	<p>EN ISO 13688:2013 4.2 (ISO 3071)</p>	<p>The pH's determination from the watery extract</p>	<p>OEKO-TEX[®] Standard 100</p>	<p>3,5 ≤pH≤ 9,5</p>
	<p>EN ISO 13688:2013 4.2 (EN 14362-1)</p>	<p>Search of the aromatic and carcinogenic amines</p>	<p>OEKO-TEX[®] Standard 100</p>	<p>≤30 ppm</p>
	<p>EN ISO 13688:2013 5.3 (ISO 5077)</p>	<p>Dimensional change to washing (40°C)</p>	<p>warp: -1.3% weft: 0.9%</p>	<p>±3%</p>

	ISO 105-C06	Colour fastness to Laundering at 40°C			1-5
		<i>Colour change</i>	4-5		
		<i>Staining:</i>			
		diacetate	4-5		
		cotton	4-5		
		nylon	4-5		
		polyester	4-5		
		acrylic	4-5		
		wool	4-5		
		ISO 105 D01	Colour fastness to to dry cleaning		
		<i>Colour change</i>	4-5		
		<i>Staining:</i>			
		diacetate	4-5		
		cotton	4-5		
		nylon	4-5		
		polyester	4-5		
		acrylic	4-5		
		wool	4-5		
		ISO 105 E04	Colour fastness to perspiration	Acidic	Alkaline
		<i>Colour change</i>	4-5	4-5	
		<i>Staining:</i>			
		diacetate	4-5	4-5	
		cotton	4-5	4-5	
		nylon	4-5	4-5	
		polyester	4-5	4-5	
		acrylic	4-5	4-5	
		wool	4-5	4-5	
		ISO 105-X12	Colour fastness to rubbing	Dry: 4-5 Wet: 3-4	
	EN ISO 105-X11	Colour fastness to hot pressing (110°C); <i>Colour change</i>	Dry: 4-5 Wet: 4-5		1-5
	ISO 105-B02	Colour fastness to light <i>Colour change:</i>	4		1-5
	EN ISO 13934-1	Tensile strength	warp: 1600 N weft: 6 20 N		
	EN ISO 13937-2	Tear strenght	warp: 44 N weft: 51 N		
	ISO 12947-2	Determination of the abrasion resistance of fabrics by the Martindale method	>30000 cycles		
Abrasion resistant inserts	EN ISO 1833-1977, SECTION 10	Composition:	100% nylon coated polyurethane		
	EN ISO 12127	Fabric mass per unit area	210 g/mq		