

Prod. Ref.	22180-000
Safety cat.	O2 WR SRC FO
Range of sizes	40 - 47 (6,5 - 12)
Weight (sz. 8)	580 g
Shape	B
Width	11

Description: Black water repellent nubuck and nylon **CORDURA**[®] ankle boot, **COFRA-TEX** waterproof membrane lining, antistatic, anti-shock, slipping resistant

Plus: COFRA-TEX water repellent membrane with **"PROOF-LINING"** construction system stitched directly to the footbed and sealed with specific glue. Waterproofness is guaranteed as well from the sealing of the polyurethane sole, which prevents water leaking. Water does not penetrate into the footwear but the vapour molecules evaporate through the membrane keeping the foot dry. **AIR** footbed, made of EVA and fabric, antistatic, anatomic, holed. It guarantees high stability thanks to its different kinds of thickness in the plantar area. Arch support made of polycarbonate and fibreglass conveniently placed between heel and sole, which provides support and protection of the plantar arch, thus preventing harmful bendings. Bellows tongue. Perfumed sole

Suggested uses: Footwear for wet environments

Care and maintenance: Clean after each use and dry off away from direct heat; treat the leather with a suitable shoe-polish. Avoid contact with aggressive chemicals or extreme temperature. Avoid immersion in sea water, lime water or cement mixed with water.



MATERIALS / ACCESSORIES

Whole footwear	Water resistance
Complete shoe	Antistatic shoe: the bottom is fit for the dissipation of electrostatic charges
Upper	Energy absorption system: polyurethane low density and heel profile Black water repellent Nubuck thickness 1,6/1,8 mm
Upper	Black water repellent nylon CORDURA [®]
Lining	COFRA-TEX membrane, breathable and abrasion resistant, colour grey thickness 1.2 mm
Insole	Antistatic, absorbent, abrasion and flaking resistant.
Sole	Antistatic dual-density polyurethane directly injected in the upper: Outsole: black, high density, slipping resistant, abrasion resistant and hydrocarbons resistant, Midsole: black, low density, comfortable and anti-shock Adherence coefficient of the sole

SAFETY TECHNICAL SPECIFICATIONS

Clause EN ISO 20347:2012	Description	Unit	Cofra result	Requirement
5.15.1	Water resistance (area of water penetration after 1000 paces in a surface flooded with water)	cm ²	≤ 3	≤ 3
6.2.2.2	Electric resistance			
	- wet	MΩ	120	≥ 0.1
	- dry	MΩ	472	≤ 1000
6.2.4	Shock absorption	J	34	≥ 20
5.4.6	Water vapour permeability	mg/cmq h	> 4,4	≥ 0,8
	Permeability coefficient	mg/cmq	> 44,5	> 15
6.3.1	Water absorption		21%	≤ 30%
	Water penetration		0,1 g	≤ 0,2 g
5.4.6	Water vapour permeability	mg/cmq h	> 2	≥ 0,8
	Permeability coefficient	mg/cmq	> 16	> 15
6.3.1	Water absorption		30%	≤ 30%
	Water penetration		0,0 g	≤ 0,2 g
5.5.3	Water vapour permeability	mg/cmq h	> 6,4	≥ 2
	Permeability coefficient	mg/cmq	> 51,2	≥ 20
5.7.4.1	Abrasion resistance	cycle	> 400	≥ 400
5.8.3	Abrasion resistance (lost volume)	mm ³	53	≤ 150
5.8.4	Flexing resistance (cut increase)	mm	1	≤ 4
5.8.6	Interlayer bond strength	N/mm	> 5	≥ 4
6.4.2	Hydrocarbons resistance (ΔV = volume increase)	%	+ 0,2	≤ 12
5.3.5	SRA : ceramic + detergent solution – flat		0,42	≥ 0,32
	SRA : ceramic + detergent solution – heel (contact angle 7°)		0,34	≥ 0,28
	SRB : steel + glycerol – flat		0,20	≥ 0,18
	SRB : steel + glycerol – heel (contact angle 7°)		0,14	≥ 0,13