

G041 - NIMBLE

Mechanical Protection Polyurethane



EN 388:2016
+A1:2018



3131X

DEXTERITY



PU-DEX

Features

- Maximum dexterity and ease of movement
- Maximum lightness and breathability
- Recommended for little tools handling

Coating

Polyurethane PU-DEX

Lining

Nylon

Gauge

13

Colour

Black/black

Application

Activities requiring superb hand dexterity, assembly, building and construction, industry, maintenance

Sizes

6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (XXL)
-----------	----------	----------	----------	------------	-------------

Lenght

21 cm	22 cm	23 cm	24 cm	25 cm	26 cm
8,3"	8,7"	9"	9,5"	9,9"	10,2"



POLYURETHANE WITH SUPERIOR GRIP



Packaging	Code	Quantity
	G041-D100	1 dozen (12 single packed gloves)
G041-DD00	1 dozen (1 bag containing 12 pairs)	
G041-K100	Carton containing 12 dozen (144 single packed gloves)	
G041-KD00	Carton containing 12 dozen (12 bags containing 12 pairs)	



New polyurethane compound that turns around the concept of grip. The excellent grasp of little tools and the maximum dexterity enhance productivity in those jobs where maximum precision and accuracy are demanded.



SAFETY TECHNICAL SPECIFICATIONS

The PPE is in compliance with essential requirements of (EU) 2016/425 regulation

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 420:2003 + A1 2009	pH determination	3,5 < pH < 9,5	6,7
UNI EN 14362-1/3:2012	Carcinogenic and aromatic amines	≤ 30 ppm	< 5
EN ISO 21420:2020	Further technical specifications applied	COMPLIANT / NOT COMPLIANT	COMPLIANT

STANDARD	DESCRIPTION	LEVEL					LEVEL REACHED	
		1	2	3	4	5		
EN 388:2016+A1:2018	Abrasion resistance (number of frictions)	≥ 100	≥ 500	≥ 2000	≥ 8000	-	3	
EN 388:2016+A1:2018	Cutting test : blade cut resistance (index)	≥ 1,2	≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	1	
EN 388:2016+A1:2018	Tear resistance (N)	≥ 10	≥ 25	≥ 50	≥ 75	-	3	
EN 388:2016+A1:2018	Puncture resistance (N)	≥ 20	≥ 60	≥ 100	≥ 150	-	1	
EN 388:2016+A1:2018 - EN ISO 13997	TDM : cutting resistance (N)	A ≥ 2	B ≥ 5	C ≥ 10	D ≥ 15	E ≥ 22	F ≥ 30	X
EN 388:2016+A1:2018 - EN 13594:2015	Impact protection	P Achieved		ABSENT Test not executed			ABSENT	

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved.