


OVERPRO WELD

Welding

LENS	Material	Polycarbonate	
	Thickness	2 mm	
	Colour	Weld 5	
	Curvature	3 	
	Standards	EN 166 - General standard EN 169 - Welding filters	
	Marking	5  1 FT 	
	Treatments		Anti-scratch treatment
FRAME	Material	Temples	Polycarbonate + nylon + TPR
	Marking	 EN 166 FT 	
	Features		Extendible temples
			Adjustable temples
FURTHER TECHNICAL FEATURES	Weight	40 g	
	Applications	Works in welding and brazing departments (gas and oxyfuel welding), foundries and furnaces.	

OVER-GLASSES TO BE USED IN COMBINATION WITH CORRECTIVE GLASSES

PERFECT ADAPTABILITY TO THE FACE



PACKAGING	<i>Code</i>		<i>Quantity</i>	
	E012-B150	Box	10 single-packed glasses	
	E012-K150	Carton	18 boxes (180 single-packed glasses)	

SAFETY TECHNICAL FEATURES						
	DESCRIPTION	STANDARDS	MINIMUM REQUIREMENT / RANGE		RESULT REACHED	MARKING
FILTER DESIGNATION	Scale number	EN166:2001 (par. 5)	---		---	5
BASIC REQUIREMENTS	Visible Light Transmission τ_v	EN169:2002 (par. 5)	3,2 % ÷ 1,2 %		2 %	---
	Optical class	EN166:2001 (par. 7.1.2.1.2)	1	On-going work	1	1
			2	Intermittent work		
			3	Occasional work (not intended for prolonged use)		
PARTICULAR REQUIREMENTS	Protection against high speed particles	EN166:2001 (par. 7.2.2)	F	Low energy impact (45 m/s)	F	F
			B	Medium energy impact (120 m/s)		
			A	High energy impact (190 m/s)		
OPTIONAL REQUIREMENTS	Protection against high speed particles at extreme temperatures	EN166:2001 (par. 7.3.4)	T	Protection against high speed particles at extreme temperatures (-5°C e +55°C)	COMPLIANT	T