





PRIME-FIT FFP2 V

DESCRIPTION	<p>The ergonomic shell-shape mask grants a remarkable adherence to the face and a comfort suitable to daily use. There are no exposed metal components; the external nosepiece used to adjust the mask on the face is metal coated. Structure and materials are long lasting and avoid the collapse in humid environments. LATEX FREE, PVC FREE.</p>			
	SIZE			One size
	CLASS			FFP2 NR
	STANDARD			EN 149:2001 + A1:2009
PACKAGING	<i>Code</i>	<i>Quantity</i>		
	M013-B021	BOX containing 20 pcs.		
	M013-K021A	CARTON containing 400 pcs. (20 boxes containing 20 pcs.)		

MATERIALS

EXTERNAL LAYER	Polyester
MELT BLOWN FILTER	Polypropylene
INTERNAL LAYER	Polyester
ELASTIC BANDS	Spandex & Nylon
EXHALATION VALVE	ABS

STOCKING CONDITIONS AND MAINTENANCE		
TEMPERATURE		Temperature between: -5°C and +38°C
MOISTURE		Moisture: < 70 %
LIFETIME *		5 years

* The lifetime refers to the unused product, stored in normal conditions in its original packaging; please read the instructions for use to be aware of maintenance and stocking instructions.

SAFETY TECHNICAL SPECIFICATIONS				
<i>Test method</i>	<i>Description</i>		<i>Result</i>	<i>Minimum requirement</i>
EN 149 (7.9.1)	Total inward leakage		3,893 % **	< 8 %
EN 149 (7.9.2)	Penetration of the filtering material (test with sodium chloride at a flow rate of 95 l/min)	Penetration after 3 minutes	0,272 % **	< 6 %
		Maximum filter penetration during the exposition to the substance	0,453 % **	
	Penetration of the filtering material (test with paraffin oil at a flow rate of 95 l/min)	Penetration after 3 minutes	0,925 % **	< 6 %
		Maximum filter penetration during the exposition to the substance	2,407 % **	
EN 149 (7.12)	Carbon dioxide content of the inhalation air		0,63 % **	< 1 %
EN 149 (7.15 / 7.16)	Inhalation resistance (flow rate of 30 l/min)		0,504 mbar **	< 0,7 mbar
	Inhalation resistance (flow rate of 95 l/min)		1,632 mbar **	< 2,4 mbar
	Exhalation resistance (flow rate of 160 l/min)		1,747 mbar **	< 3,0 mbar
ASTM D5712-99	Standard test method for analysis of proteins in natural rubber and its products		NOT DETECTED	-

** The results refer to the arithmetic mean of the data of the test reports EN 149:2001 + A1:2009. The highest result is lower than the minimum requirement