

## REDIG FAST

Anatomical positioning belt equipped with adjustment quick-release buckle. Two side attachment points for work positioning and restraint.

### STANDARD

EN358:2018

### ATTACHMENT POINTS

Lateral: two D-ring made of zinc-plated steel closeable with Reverse-D technology

### ADJUSTMENT

Belt: a quick-release buckle made of coated steel

### PLUS

Back Support: sponge with 3D-PERSPIREX technology



## PLUS – TECHNOLOGIES – MATERIALS



### EXTREME LOAD 150 kg

The additional test certifies the resistance of Cofra devices against a maximum nominal load of 150 kg, compared with the 100 kg of the normal devices on the market.



### REVERSE-D

Thanks to REVERSE-D technology, attachment points can be folded away and closed at any time, and whenever they are not needed. The ability to shut away attachment points prevents the user from remaining accidentally stuck or caught on protrusions and dangerous snags.



### 3D-PERSPIREX

3D-Perspirex technology takes advantage from three-dimensional weave of the coating sponge to increase total breathability and comfort for the end user.



### QUICK-RELEASE BUCKLES

Quick-release buckles offer the user fast and easy locking while maintaining high resistance to stresses.



### HIGH-TENACITY POLYESTER STRAP

The strap is made of high-tenacity polyester making it highly resistant to tear and abrasion.




### STEEL COMPONENTS

Steel resists perfectly to the considerable stresses which develop during a fall. All steel components have undergone anticorrosive galvanisation treatment with zinc or chrome.

## PACKAGING

| Code         | Size  | Quantity | Weight (pc.) |
|--------------|-------|----------|--------------|
| A006-1101.I4 | S-3XL | 1 pc.    | 635 g        |
| A006-K101.I4 |       | 26 pcs.  |              |

| SIZE                                                                              |        |
|-----------------------------------------------------------------------------------|--------|
|  | BELTS  |
|                                                                                   | B (cm) |
| S-3XL                                                                             | 80/130 |

## STOCKING CONDITIONS AND MAINTENANCE

### LIFETIME

The lifetime of the unused metal products is unlimited. The lifetime of the unused not metal products is 10 years under normal conditions. Once the product is used, its lifetime cannot be estimated since there are factors which could considerably reduce its lifetime such as: intense use; damage to product components; contact with chemical substances; high temperatures, abrasions, cuts, violent impacts, wrong use and stockage.

### CLEANING

**Cleaning the textile and plastic parts:** wash only with cold fresh water and neutral soap and allow to air dry, away from direct sources of heat.

**Cleaning the metallic parts:** wash with cold fresh water and dry. If the equipment becomes wet either during use or after cleaning, it must be left to air dry and kept away from direct heat.

### TRANSPORT AND STOCKING

Keep the device in its original packaging. During transport and storage, keep this product away from light and sources of heat, from high humidity, from sharp edges or objects, from corrosive substances and from any other possible cause of damage or deterioration, in order to preserve the performance and safety of the product. Keep this product in a cool, dry place to preserve the performance and safety of the product.