






ROUNDFIT

Classic

LENS	Material	Polycarbonate	
	Thickness	2 mm	
	Colour	Clear SF	
	Curvature	10 	
	Standards	EN 166 - General standard EN 170 - Ultraviolet filters	
	Marking	2C-1,2  1 FT CE	
	Treatments		Anti-scratch treatment
		Anti-fog treatment	
FRAME	Material	Temples	Polycarbonate
	Marking	 EN 166 FT CE	
FURTHER TECHNICAL FEATURES	Weight	24 g	
	Applications	Mechanical indoor work with good visibility conditions.	

EXCELLENT LIGHTNESS
PERFECT ADAPTABILITY TO THE FACE



PACKAGING	<i>Code</i>		<i>Quantity</i>	
	E005-B101	Box	10 single-packed glasses	
	E005-K101	Carton	24 boxes (240 single-packed glasses)	

SAFETY TECHNICAL FEATURES

	DESCRIPTION	STANDARDS	MINIMUM REQUIREMENT / RANGE		RESULT REACHED	MARKING
FILTER DESIGNATION	Scale number	EN166:2001 (par. 5)	---		---	2C - 1,2
BASIC REQUIREMENTS	Visible Light Transmission τ_v	EN170:2002 (par. 5)	100 % ÷ 74,4 %		92 %	---
	Optical class	EN166:2001 (par. 7.1.2.1.2)	1	On-going work	1	1
			2	Intermittent work		
3			Occasional work (not intended for prolonged use)			
PARTICULAR REQUIREMENTS	Protection against high speed particles	EN166:2001 (par. 7.2.2)	F	Low energy impact (45 m/s)	F	F
			B	Medium energy impact (120 m/s)		
			A	High energy impact (190 m/s)		
OPTIONAL REQUIREMENTS	Protection against high speed particles at extreme temperatures	EN166:2001 (par. 7.3.4)	T	Protection against high speed particles at extreme temperatures (-5°C e +55°C)	COMPLIANT	T