








SOFYTOUCH-V

Goggle

LENS	Material	Polycarbonate	
	Thickness	2 mm	
	Colour	Clear	
	Curvature	5 	
	Standards	EN 166 - General standard EN 170 - Ultraviolet filters	
	Marking	 1 BT 9 CE	
	Treatments		Anti-scratch treatment
		Anti-fog treatment	
FRAME	Material	Front	PVC
	Marking	 EN 166 3 4 9 BT CE	
	Features		Ventilation system
FURTHER TECHNICAL FEATURES	Weight	108 g	
	Applications	Mechanical indoor work with good visibility conditions.	

**COMPATIBLE WITH THE USE OF
CORRECTIVE GLASSES AND DUST
MASKS**

**VENTILATION SYSTEM
EXCELLENT COMFORT**



PACKAGING	<i>Code</i>		<i>Quantity</i>	
	E015-B100	Box	5 single-packed glasses	
	E015-K100	Carton	12 boxes (60 single-packed glasses)	

SAFETY TECHNICAL FEATURES

	DESCRIPTION	STANDARDS	MINIMUM REQUIREMENT / RANGE		RESULT REACHED	MARKING
FILTER DESIGNATION	Scale number	EN166:2001 (par. 5)	---		---	---
BASIC REQUIREMENTS	Visible Light Transmission τ_v	EN170:2002 (par. 5)	100 % \div 74,4 %		92 %	---
	Optical class	EN166:2001 (par. 7.1.2.1.2)	1	On-going work	1	1
			2	Intermittent work		
			3	Occasional work (not intended for prolonged use)		
PARTICULAR REQUIREMENTS	Protection against high speed particles	EN166:2001 (par. 7.2.2)	F	Low energy impact (45 m/s)	B	B
			B	Medium energy impact (120 m/s)		
			A	High energy impact (190 m/s)		
	Protection against droplets and liquid splashes	EN166:2001 (par. 7.2.4)	3	Droplets of liquid	COMPLIANT	3
	Protection against dust particles of big dimensions	EN166:2001 (par. 7.2.5)	4	Powder with particles > 5 μ m	COMPLIANT	4
	Protection against molten metals and hot solids	EN166:2001 (par. 7.2.3)	9	Liquid metal splashes and penetration of hot solids	COMPLIANT	9
OPTIONAL REQUIREMENTS	Protection against high speed particles at extreme temperatures	EN166:2001 (par. 7.3.4)	T	Protection against high speed particles at extreme temperatures (-5°C e +55°C)	COMPLIANT	T