

STEELY

Classic

LENS	Material	Polycarbonate	
	Thickness	2 mm	
	Colour	Grey	
	Curvature	4 	
	Standards	EN 166 - General standard EN 172 - Solar protection filters for industrial use	
	Marking	5-3,1  1 FT C€	
FRAME	Material	Front	Nylon
		Temples	Nylon
	Marking	 EN 166 FT C€	
	Features		Extendible temples
FURTHER TECHNICAL FEATURES	Weight	33 g	
	Applications	Outdoor works, mechanical works with risk of glare, agriculture, building, refineries.	

COMPLETE EYE PROTECTION



PACKAGING	Code	Quantity	
	E010-B110	Box	10 single-packed glasses
	E010-K110	Carton	24 boxes (240 single-packed glasses)

SAFETY TECHNICAL FEATURES						
	DESCRIPTION	STANDARDS	MINIMUM REQUIREMENT / RANGE		RESULT REACHED	MARKING
FILTER DESIGNATION	Scale number	EN166:2001 (par. 5)	---		---	5 - 3,1
BASIC REQUIREMENTS	Visible Light Transmission τ_v	EN172:1994 + A1:2000 + A2:2001 (par. 4)	17,8 % ÷ 8,0 %		13 %	---
	Optical class	EN166:2001 (par. 7.1.2.1.2)	1	On-going work	1	1
			2	Intermittent work		
			3	Occasional work (not intended for prolonged use)		
PARTICULAR REQUIREMENTS	Protection against high speed particles	EN166:2001 (par. 7.2.2)	F	Low energy impact (45 m/s)	F	F
			B	Medium energy impact (120 m/s)		
			A	High energy impact (190 m/s)		
OPTIONAL REQUIREMENTS	Protection against high speed particles at extreme temperatures	EN166:2001 (par. 7.3.4)	T	Protection against high speed particles at extreme temperatures (-5°C e +55°C)	COMPLIANT	T