








# WIDELAMP

## Sports

LENS	Material	Polycarbonate	
	Thickness	2,15 mm	
	Colour	Clear	
	Curvature	8 	
	Standards	EN 166 - General standard EN 170 - Ultraviolet filters	
	Marking	2C-1,2  1 F 	
	Treatments		Anti-scratch treatment
		Anti-fog treatment	
FRAME	Material	Front	Nylon
		Temples	Polycarbonate + TPR
		Nase pad	TPR
	Marking	 EN 166 F 	
	Features		Soft nose pad
			Soft ear pieces
FURTHER TECHNICAL FEATURES	Weight	48 g	
	Applications	Mechanical indoor work with good visibility conditions, works in dark or poorly lit areas, electric, hydraulic and domestic works, mechanical repairs.	

LED INTEGRATED INTO THE TEMPLES

SOFT SLIP RESISTANT TEMPLES



BATTERIES INCLUDED

<b>PACKAGING</b>	Code		Quantity	
	<b>E022-B100</b>	Box	5 single-packed glasses	
	<b>E022-K100</b>	Carton	24 boxes (120 single-packed glasses)	

SAFETY TECHNICAL FEATURES						
	DESCRIPTION	STANDARDS	MINIMUM REQUIREMENT / RANGE		RESULT REACHED	MARKING
<b>FILTER DESIGNATION</b>	Scale number	EN166:2001 (par. 5)	---		---	<b>2C - 1,2</b>
<b>BASIC REQUIREMENTS</b>	Visible Light Transmission $\tau_v$	EN170:2002 (par. 5)	100 % $\div$ 74,4 %		90 %	---
	Optical class	EN166:2001 (par. 7.1.2.1.2)	1	On-going work	1	<b>1</b>
			2	Intermittent work		
			3	Occasional work (not intended for prolonged use)		
<b>PARTICULAR REQUIREMENTS</b>	Protection against high speed particles	EN166:2001 (par. 7.2.2)	F	Low energy impact (45 m/s)	F	<b>F</b>
			B	Medium energy impact (120 m/s)		
			A	High energy impact (190 m/s)		