

ROCKHAMPTON

<p>Description</p>	<p>ROCKHAMPTON anchorage tapes made of a 30 mm wide webbing can be mounted on horizontal structures such as beams or tubes with the "stitched loop end" and "double ribbon hook" methods; the static breakage load registered during checks is 22 kN and 30 kN respectively. It is essential that installers confirm the suitability of the support and that portable temporary anchorages are used by only one person at a time and with an energy absorber.</p>			
<p>Standard</p>	<p>EN795-B</p>			
<p>Strap</p>	<p>30 mm wide polyester</p>			
<p>Static breaking load with stitched loop end assembly</p>	<p>22 kN</p>			
<p>Static breaking load with hook assembly</p>	<p>30 kN</p>			
<p>Packaging</p>	<p>Code</p>	<p>Quantity</p>	<p>Weight (pc.)</p>	<p>Length</p>
	<p>A050-B100</p>	<p>Bag containing 5 pcs.</p>	<p>55 g</p>	<p>60 cm</p>
	<p>A050-K100</p>	<p>300 pcs. (60 bags containing 5 pcs.)</p>		
	<p>A050-B101</p>	<p>Bag containing 5 pcs.</p>	<p>71 g</p>	<p>80 cm</p>
	<p>A050-K101</p>	<p>250 pcs. (50 bags containing 5 pcs.)</p>		
	<p>A050-B102</p>	<p>Bag containing 5 pcs.</p>	<p>105 g</p>	<p>120 cm</p>
	<p>A050-K102</p>	<p>175 pcs. (35 bags containing 5 pcs.)</p>		
	<p>A050-B103</p>	<p>Bag containing 5 pcs.</p>	<p>132 g</p>	<p>150 cm</p>
<p>A050-K103</p>	<p>150 pcs. (30 bags containing 5 pcs.)</p>			

STOCKING CONDITIONS AND MAINTENANCE

Lifetime	The lifetime of the unused metal products is unlimited. The lifetime of the unused not metal products is 10 years under normal conditions. Once the product is used, its lifetime cannot be estimated since there are factors which could considerably reduce its lifetime such as: intense use; damage to product components; contact with chemical substances; high temperatures, abrasions, cuts, violent impacts, wrong use and stockage.
Cleaning	Cleaning the textile and plastic parts: wash only with cold fresh water and neutral soap and allow to air dry, away from direct sources of heat. If the equipment becomes wet either during use or after cleaning, it must be left to air dry and kept away from direct heat.
Transport and stocking	Keep the device in its original packaging. During transport and storage, keep this product away from light and sources of heat, from high humidity, from sharp edges or objects, from corrosive substances and from any other possible cause of damage or deterioration, in order to preserve the performance and safety of the product. Keep this product in a cool, dry place to preserve the performance and safety of the product.