

MYGRAB		
Description	<p>Restraint and work positioning lanyard certified with a mass of 150 kg . It is simple to be used and it is possible to change its length during any working phase thanks to its sliding length adjustment with an ergonomic lever and automatic locking system. Steel connectors.</p>	
Locking system	<p style="text-align: center;">SCREW</p> 	<p>The Screw lock is the simplest locking mechanism while maintaining a high level of safety.</p>
Plus	<p>EXTREME LOAD 150 Kg</p> 	<p>The additional test certifies the resistance of Cofra devices against a maximum nominal load of 150 kg, compared with the 100 kg of the normal devices on the market.</p>
	<p>KERNMANTLE ROPE</p> 	<p>The static rope with kernmantle weave is characterised by a composite structure comprising a stress-resistant inner kern and an outer mantle to protect the kern from abrasion, UV rays, weather conditions, oil, fire and heat. In addition, the mantle acts as a visible indicator of the rope's wear.</p>
	<p>STEEL COMPONENTS</p> 	<p>Steel resists perfectly to the considerable stresses which develop during a fall. All steel components have undergone anticorrosive galvanisation treatment with zinc or chrome.</p>
	<p>ALUMINIUM COMPONENTS</p> 	<p>Aluminium is a very light metal offering the same mechanical performance as steel. It resists the considerable stresses which develop during a fall. All aluminium components have undergone anticorrosive anodization treatment.</p>
Standard	EN358:2018	

	Code	Quantity	Packaging	Weight (pc.)	Length MAX	Length MIN
Packaging	A026-1101	1 pc.	one piece	890 g	2 m	0,6 m
	A026-K101	20 pcs.				
	A026-1102	1 pc.	one piece	1000 g	3 m	0,6 m
	A026-K102	18 pcs.				
	A026-1103	1 pc.	one piece	1100 g	4 m	0,6 m
	A026-K103	15 pcs.				
	A026-1104	1 pc.	one piece	1210 g	5 m	0,6 m
	A026-K104	15 pcs.				
	A026-1105	1 pc.	one piece	1720 g	10 m	0,6 m
	A026-K105	10 pcs.				

ROPE		
Diameter	12 mm	
Type	Rope with kernmantle weave	
Material	Inner kern: Polyester	
	Outer mantle: Polyester	
ADJUSTMENT SYSTEM		
Type	Sliding adjustment system	
Material	Aluminium	
CONNECTORS	Connector at the end of the adjustment system	Free end connector
Description	Base connector	End connector
Standard	EN362-B	EN362-T
Material	Zinc-plated steel	Zinc-plated steel
Opening	18 mm	19 mm
Locking system	SCREW - Screw lock	Back safety lever
Minimum resistance for the major axis with closed and locked lever	25 kN	23 kN

STOCKING CONDITIONS AND MAINTENANCE

Lifetime	The lifetime of the unused metal products is unlimited. The lifetime of the unused not metal products is 10 years under normal conditions. Once the product is used, its lifetime cannot be estimated since there are factors which could considerably reduce its lifetime such as: intense use; damage to product components; contact with chemical substances; high temperatures, abrasions, cuts, violent impacts, wrong use and stockage.
Cleaning	<p>Cleaning the textile and plastic parts: wash only with cold fresh water and neutral soap and allow to air dry, away from direct sources of heat.</p> <p>Cleaning the metallic parts: wash with cold fresh water and dry.</p> <p>Lubrication: lubricate the lever mechanism with silicone based lubricants.</p> <p>If the equipment becomes wet either during use or after cleaning, it must be left to air dry and kept away from direct heat.</p>
Transport and stocking	Keep the device in its original packaging. During transport and storage, keep this product away from light and sources of heat, from high humidity, from sharp edges or objects, from corrosive substances and from any other possible cause of damage or deterioration, in order to preserve the performance and safety of the product. Keep this product in a cool, dry place to preserve the performance and safety of the product.